HT Power Cable CouplerMedium Voltage Mining Application





Current Rating: Upto 400A Voltage Rating: 3.3KV /6.6KV/12KV

Frequency: 50Hz/60z

3.3KV /6.6KV/12KV cable couplers offer the widest range of features and options available in the product.

These couplers can be used in wet and dusty environments FEATURES & BENEFITS

i) All copper parts are Nickel plated to prevent conductor oxidation.

Cable adapter provides stress control and dust free seal on cable termination.

COUPLER ACCESSORIES(OPTIONAL)

- i) Castle inter lock
- ii) Cover with chain arrangement STANDARDS:
- i) The design corresponds to the latest specification A.S 1300-2009:
 - ii) Manufactured to meet IP65 design standards.
 - iii) Individual phase insulators made of high dielectric materials.
 - iv) The casting is rust free and non-corrosive material.

TESTED:

- i) CPRI for Short time current rating of 40KA
- ii) CPRI for Basic Insulation Level of 95KV
 - iii) Couplers are tested for IP 65.
 - iv) CPRI for Temperature Rise
 - v) CPRI for Low Partial discharge

Note:-

- 1. Current Rating can be increased to 630A, if desired.
- 2. As continuous developments are made of all Panickker products, equipment supplied may differ in detail from the described above.

PANICKKER SWITCHGEAR P. LTD

25, JANAKIRAM COLONY

ARUMBAKKAM

CHENNAI-600106

TEL:+91 44 23636754

+91 9444380999

+91 9551696720